

QN0805X224J3950FB

R25=220kΩ±5%， B25/50=3950±1%， B25/85=4010

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	6,511.235	7,096.199	7,714.381	8.71%	1.27
-39	6,106.991	6,651.330	7,226.078	8.64%	1.27
-38	5,730.227	6,236.971	6,771.557	8.57%	1.27
-37	5,378.925	5,850.862	6,348.295	8.50%	1.27
-36	5,051.224	5,490.922	5,953.972	8.43%	1.27
-35	4,745.411	5,155.235	5,586.451	8.36%	1.27
-34	4,459.902	4,842.033	5,243.764	8.30%	1.27
-33	4,193.241	4,549.690	4,924.098	8.23%	1.27
-32	3,944.079	4,276.701	4,625.780	8.16%	1.27
-31	3,711.174	4,021.680	4,347.271	8.10%	1.27
-30	3,493.376	3,783.348	4,087.146	8.03%	1.27
-29	3,289.625	3,560.522	3,844.093	7.96%	1.26
-28	3,098.938	3,352.110	3,616.900	7.90%	1.26
-27	2,920.407	3,157.101	3,404.446	7.83%	1.26
-26	2,753.192	2,974.562	3,205.695	7.77%	1.26
-25	2,596.515	2,803.627	3,019.691	7.71%	1.26
-24	2,449.655	2,643.498	2,845.547	7.64%	1.26
-23	2,311.945	2,493.433	2,682.444	7.58%	1.26
-22	2,182.766	2,352.746	2,529.623	7.52%	1.26
-21	2,061.543	2,220.801	2,386.381	7.46%	1.25
-20	1,947.744	2,097.008	2,252.066	7.39%	1.25
-19	1,840.876	1,980.820	2,126.075	7.33%	1.25
-18	1,740.479	1,871.731	2,007.848	7.27%	1.25
-17	1,646.127	1,769.267	1,896.865	7.21%	1.25
-16	1,557.425	1,672.993	1,792.645	7.15%	1.25
-15	1,474.004	1,582.502	1,694.739	7.09%	1.24
-14	1,395.522	1,497.415	1,602.732	7.03%	1.24

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	1,321.661	1,417.383	1,516.237	6.97%	1.24
-12	1,252.124	1,342.077	1,434.895	6.92%	1.24
-11	1,186.637	1,271.194	1,358.373	6.86%	1.24
-10	1,124.940	1,204.452	1,286.360	6.80%	1.24
-9	1,066.797	1,141.587	1,218.566	6.74%	1.23
-8	1,011.983	1,082.353	1,154.723	6.69%	1.23
-7	960.291	1,026.523	1,094.579	6.63%	1.23
-6	911.526	973.882	1,037.902	6.57%	1.23
-5	865.508	924.232	984.473	6.52%	1.23
-4	822.068	877.388	934.090	6.46%	1.22
-3	781.048	833.177	886.563	6.41%	1.22
-2	742.301	791.437	841.716	6.35%	1.22
-1	705.689	752.017	799.383	6.30%	1.22
0	671.084	714.777	759.412	6.24%	1.21
1	638.366	679.586	721.658	6.19%	1.21
2	607.421	646.319	685.988	6.14%	1.21
3	578.146	614.862	652.274	6.08%	1.21
4	550.441	585.107	620.401	6.03%	1.20
5	524.214	556.953	590.258	5.98%	1.20
6	499.379	530.307	561.743	5.93%	1.20
7	475.855	505.080	534.760	5.88%	1.20
8	453.566	481.189	509.218	5.82%	1.19
9	432.441	458.557	485.034	5.77%	1.19
10	412.414	437.111	462.128	5.72%	1.19
11	393.422	416.783	440.427	5.67%	1.18
12	375.406	397.509	419.861	5.62%	1.18
13	358.312	379.230	400.365	5.57%	1.18
14	342.087	361.888	381.879	5.52%	1.18
15	326.683	345.432	364.344	5.47%	1.17
16	312.055	329.812	347.707	5.43%	1.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	298.159	314.980	331.918	5.38%	1.17
18	284.956	300.894	316.930	5.33%	1.16
19	272.407	287.513	302.697	5.28%	1.16
20	260.477	274.797	289.179	5.23%	1.16
21	249.132	262.710	276.335	5.19%	1.15
22	238.340	251.218	264.129	5.14%	1.15
23	228.073	240.289	252.526	5.09%	1.15
24	218.302	229.892	241.493	5.05%	1.14
25	209.000	220.000	231.000	5.00%	1.14
26	199.968	210.585	221.211	5.05%	1.16
27	191.373	201.621	211.887	5.09%	1.18
28	183.192	193.086	203.005	5.14%	1.19
29	175.403	184.956	194.541	5.18%	1.21
30	167.986	177.210	186.473	5.23%	1.23
31	160.920	169.828	178.782	5.27%	1.25
32	154.188	162.792	171.447	5.32%	1.26
33	147.772	156.084	164.451	5.36%	1.28
34	141.655	149.686	157.777	5.41%	1.30
35	135.823	143.583	151.407	5.45%	1.32
36	130.261	137.760	145.327	5.49%	1.34
37	124.955	132.203	139.522	5.54%	1.36
38	119.892	126.898	133.978	5.58%	1.38
39	115.060	121.833	128.683	5.62%	1.39
40	110.447	116.996	123.624	5.67%	1.41
41	106.042	112.375	118.789	5.71%	1.43
42	101.835	107.960	114.168	5.75%	1.45
43	97.815	103.741	109.750	5.79%	1.47
44	93.975	99.707	105.524	5.83%	1.49
45	90.305	95.851	101.483	5.88%	1.51
46	86.796	92.163	97.617	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	83.441	88.635	93.917	5.96%	1.55
48	80.233	85.260	90.376	6.00%	1.57
49	77.164	82.030	86.985	6.04%	1.59
50	74.227	78.938	83.739	6.08%	1.61
51	71.416	75.979	80.630	6.12%	1.63
52	68.726	73.145	77.652	6.16%	1.65
53	66.151	70.430	74.799	6.20%	1.67
54	63.684	67.830	72.064	6.24%	1.69
55	61.322	65.338	69.443	6.28%	1.71
56	59.059	62.950	66.930	6.32%	1.73
57	56.890	60.661	64.520	6.36%	1.75
58	54.812	58.466	62.208	6.40%	1.77
59	52.819	56.362	59.991	6.44%	1.79
60	50.909	54.343	57.864	6.48%	1.81
61	49.077	52.406	55.822	6.52%	1.83
62	47.320	50.548	53.862	6.56%	1.85
63	45.634	48.765	51.980	6.59%	1.88
64	44.016	47.053	50.173	6.63%	1.90
65	42.464	45.409	48.438	6.67%	1.92
66	40.973	43.831	46.771	6.71%	1.94
67	39.542	42.315	45.169	6.75%	1.96
68	38.168	40.859	43.630	6.78%	1.98
69	36.848	39.460	42.151	6.82%	2.00
70	35.580	38.115	40.729	6.86%	2.03
71	34.362	36.823	39.361	6.89%	2.05
72	33.191	35.580	38.046	6.93%	2.07
73	32.066	34.386	36.781	6.97%	2.09
74	30.984	33.237	35.564	7.00%	2.11
75	29.943	32.132	34.393	7.04%	2.14
76	28.943	31.068	33.267	7.08%	2.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	27.980	30.045	32.182	7.11%	2.18
78	27.054	29.061	31.138	7.15%	2.20
79	26.163	28.113	30.132	7.18%	2.23
80	25.306	27.201	29.164	7.22%	2.25
81	24.481	26.322	28.231	7.25%	2.27
82	23.686	25.476	27.333	7.29%	2.30
83	22.921	24.661	26.467	7.32%	2.32
84	22.184	23.876	25.633	7.36%	2.34
85	21.474	23.119	24.828	7.39%	2.36
86	20.790	22.390	24.053	7.43%	2.39
87	20.131	21.687	23.306	7.46%	2.41
88	19.496	21.010	22.585	7.50%	2.44
89	18.884	20.357	21.889	7.53%	2.46
90	18.294	19.727	21.219	7.56%	2.48
91	17.725	19.119	20.572	7.60%	2.51
92	17.176	18.533	19.947	7.63%	2.53
93	16.647	17.968	19.345	7.66%	2.55
94	16.137	17.422	18.763	7.70%	2.58
95	15.644	16.895	18.201	7.73%	2.60
96	15.169	16.387	17.659	7.76%	2.63
97	14.710	15.896	17.136	7.80%	2.65
98	14.267	15.423	16.630	7.83%	2.68
99	13.840	14.965	16.141	7.86%	2.70
100	13.427	14.523	15.669	7.89%	2.73
101	13.028	14.096	15.213	7.93%	2.75
102	12.643	13.684	14.772	7.96%	2.78
103	12.271	13.285	14.346	7.99%	2.80
104	11.912	12.900	13.935	8.02%	2.83
105	11.565	12.527	13.536	8.05%	2.85
106	11.229	12.168	13.151	8.08%	2.88

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	10.905	11.820	12.779	8.12%	2.90
108	10.591	11.483	12.419	8.15%	2.93
109	10.288	11.158	12.070	8.18%	2.95
110	9.995	10.843	11.733	8.21%	2.98
111	9.712	10.538	11.407	8.24%	3.00
112	9.437	10.244	11.091	8.27%	3.03
113	9.172	9.958	10.785	8.30%	3.06
114	8.915	9.682	10.489	8.33%	3.08
115	8.667	9.415	10.203	8.36%	3.11
116	8.427	9.157	9.925	8.39%	3.14
117	8.194	8.906	9.656	8.42%	3.16
118	7.969	8.664	9.396	8.45%	3.19
119	7.751	8.429	9.144	8.48%	3.21
120	7.540	8.202	8.900	8.51%	3.24
121	7.335	7.981	8.663	8.54%	3.27
122	7.137	7.768	8.434	8.57%	3.30
123	6.945	7.561	8.211	8.60%	3.32
124	6.759	7.361	7.996	8.63%	3.35
125	6.579	7.166	7.787	8.66%	3.38